

<b>RESILIENT SEATED BUTTERFLY VALVES</b>			
<b>VALVE SIZE</b>	<b>WAFFER STUDS</b>	<b>LUG STUDS</b>	<b>BOLT LUG</b>
2"	5/8-11 X 5" LONG	5/8-11 X 2.5" LONG	5/8-11 X 1.5" LONG
2.5"	5/8-11 X 5.25" LONG	5/8-11 X 2.75" LONG	5/8-11 X 1.75" LONG
3"	5/8-11 X 5.5" LONG	5/8-11 X 2.75" LONG	5/8-11 X 1.75" LONG
4"	5/8-11 X 5.75" LONG	5/8-11 X 3" LONG	5/8-11 X 1.88" LONG
5"	3/4-10 X 6" LONG	3/4-10 X 3" LONG	3/4-10 X 2" LONG
6"	3/4-10 X 6" LONG	3/4-10 X 3" LONG	3/4-10 X 2" LONG
8"	3/4-10 X 6.5" LONG	3/4-10 X 3.25" LONG	3/4-10 X 2.25" LONG
10"	7/8-9 X 7.25" LONG	7/8-9 X 3.75" LONG	7/8-9 X 2.38" LONG
12"	7/8-9 X 7.75" LONG	7/8-9 X 4" LONG	7/8-9 X 2.75" LONG
14"	1-8 X 8.75" LONG	1-8 X 4.5" LONG	1-8 X 2.75" LONG
16"	1-8 X 9.25" LONG	1-8 X 4.75" LONG	1-8 X 3" LONG
18"	1 1/8-7 X 10.5" LONG	1 1/8-7 X 5.25" LONG	1 1/8-7 X 3.5" LONG
20"	1 1/8-7 X 11.75" LONG	1 1/8-7 X 6" LONG	1 1/8-7 X 4.25" LONG
24"	1 1/4-7 X 13.25" LONG	1 1/4-7 X 6.75" LONG	1 1/4-7 X 4.75" LONG
CONSULT WITH FACTORY FOR VALVES LARGER THAN 24"			
A-T CONTROLS RECOMMENDS USING STUDS TO ENSURE FULL ENGAGEMENT IN TAPPED HOLES.			
IT IS THE END USERS RESPONSIBILITY TO SELECT THE CORRECT MATERIAL AND GRADE OF FASTNERS FOR THEIR APPLICATION.			