



Note:

- "+" connects to 1, "-" connects to 3.
"-" connects to 7 for heater.
- S1 comes On for open.
Off for close.
- Using less than 5A current for "A~F".

THE DESIGN AND DISCLOSURE CONTAINED IN THIS DRAWING WAS ORIGINATED BY, AND IS EXCLUSIVE PROPERTY OF A-T CONTROLS, INC. IT IS FURNISHED FOR VENDOR INFORMATION ONLY AND IS NOT AN AUTHORIZATION -OR- LICENSE TO MAKE THIS CONSTRUCTION OR TO FURNISH THIS INFORMATION TO OTHERS. ALL DRAWINGS MUST BE RETURNED TO A-T CONTROLS, INC. ON DEMAND. THIS DRAWING IS NOT TO BE REPRODUCED OR COPIED IN ANY FORM WITHOUT THE EXPRESS WRITTEN PERMISSION OF A-T CONTROLS, INC.



Division of A-T Controls, Inc.
11363 Deerfield Road
Cincinnati, Ohio 45242
Phone: (513) 247-5465
Fax: (513) 247-5462

DRAWN SAH	CHECKED BY	APPROVED
DATE 10/16/07	DATE	DATE
TITLE FSE SERIES WIRING DIAGRAM SPRING RETURN ELECTRIC ACTUATOR 24VDC		

1652	11/20/15	SAH
ECN#	DATE	BY

